


|              | 文件类型  | 技术文件                      | 文件版本 | V3.10.0                  |     |            |
|---|---|---------------------------|------|--------------------------|-----|------------|
|   | 项目代号  | /                         | 页码   | 第0页, 共1页                 |     |            |
|   | 文件编号  | GL DM-56-61-en            |      |                          |     |            |
| 文件名称:<br><p style="text-align: center;"><b>CALIBRATOR CPF1025 2025-11-10</b></p> 适用范围: 1117项目 |   |                           |      |                          |     |            |
| 编制: 刘金盈<br>日期: 2025.09.23   |   | 审核: 冯会娟<br>日期: 2025.09.23 |      | 批准: 程军<br>日期: 2025.09.23 |     |            |
| 修 订 记 录   |   |                           |      |                          |     |            |
| 版本  | TCN/ECR/PCN编号   | 修订内容概要                    |      | 修改人                      | 批准人 | 批准日期       |
| V3.10.0   | /   | 新建                        |      | 刘金盈                      | 程军  | 2025.09.23 |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
|   |   |                           |      |                          |     |            |
| 发至:   | <input type="checkbox"/> 总经办 <input type="checkbox"/> 质量部 <input type="checkbox"/> 财务部 <input checked="" type="checkbox"/> 营销部 <input checked="" type="checkbox"/> 客服 <input type="checkbox"/> 计划 <input type="checkbox"/> 采购 <input checked="" type="checkbox"/> 工程 <input type="checkbox"/> 仓库<br><br><input checked="" type="checkbox"/> 设备研发 <input checked="" type="checkbox"/> 试剂研发 <input type="checkbox"/> 物料质量 <input type="checkbox"/> 设备生产 <input type="checkbox"/> 试剂生产 <input checked="" type="checkbox"/> 试剂质检 <input checked="" type="checkbox"/> 设备质检 |                           |      |                          |     |            |
| 由工程   |   |                           |      |                          |     |            |

# DM-CAL-PF

## HEMATOLOGY CALIBRATOR

Reference Values provided by DYMIND

**CALIBRATOR**

LOT CPF1025

2025-09-12

2025-11-10

| Applicable Instruments  | Parameter | Unit            | Reference Value |
|---|-----------|-----------------|-----------------|
| DYMIND<br><br>DH-800 series<br>DH-800 CRP series<br>DH-800 CS series<br>(Technical File Version A1.3 or higher) | PLT-F     | $\times 10^9/L$ | 190             |

**【NOTE】**

1. The calibrator should be stored in refrigerator (2°C~8°C). After opening, it will keep stable for 7 days when it is stored airtight at 2°C~8°C.
2. Before mixing and running the calibrator after take it out from the refrigerator, please keep it at least 15 minutes until reaching room temperature(15°C~30°C).
3. Calibrator must be well mixed before using. Please mix gently, to avoid cells rupture and/or generating bubbles.
4. After using, put the calibrator back into the refrigerator to prevent contamination and evaporation.